

OPTIONAL STOCKED STYLES



804-4254

16" LINEMAN'S BOOT COMPOSITE SAFETY TOE

UPPER: Brown Full Grain Oil Tanned Leather

CONSTRUCTION: Goodyear Storm Welt

INSOLE: Removable Dual Density Ultimate Shock Absorption™ Footbed on Poron® 4000 Comfort Cushion

MIDSOLE: Rubber

SHANK: Steel Triple Ladder Shank with Half Slip Wedge for Better Arch Support

OUTSOLE: Vibram® Austin Oil Resisting Rubber Mini-Lug

SPECIAL FEATURES: ASTM F 2413-05 M/I/75/C/75 [Composite Safety Toe](#). Electrical Hazard. [Tested for and Meets CAN/CSA-Z195 18,000 Volts Electric Shock Resistance Standard](#). Removable Kiltie and Double Leather Pole Guard. Made in USA by ISO 9001 Certified Shoe Company.

MEN'S SIZES

D 8-12, 13, 14

E 9-12, 13, 14

EE 8-12, 13



804-6370

10" LINEMAN'S BOOT COMPOSITE SAFETY TOE

UPPER: Black Full Grain Oil Tanned Leather

CONSTRUCTION: Goodyear Storm Welt

INSOLE: Removable Dual Density Ultimate Shock Absorption™ Footbed on Poron® 4000 Comfort Cushion

MIDSOLE: Rubber

SHANK: Steel Triple Ladder Shank with Half Slip Wedge for Better Arch Support

OUTSOLE: Vibram® Austin Oil Resisting Rubber Mini-Lug

SPECIAL FEATURES: ASTM F 2413-05 M/I/75/C/75 [Composite Safety Toe](#). Electrical Hazard. [Tested for and Meets CAN/CSA-Z195 18,000 Volts Electric Shock Resistance Standard](#). Removable Kiltie and Double Leather Pole Guard. Made in USA by ISO 9001 Certified Shoe Company.

M 7-12, 13, 14

W 7-12, 13, 14



804-4240

6" BROWN GEN EX™ SAFETY

UPPER: Brown Oiled Nubuck

CONSTRUCTION: Goodyear Welt

LINING: Dri-Lex® Aerospacer®

INSOLE: Polyurethane Removable Insert/Special EVA Cushion Flex

MIDSOLE: Shock Absorbing EVA **SHANK:** Composite

OUTSOLE: GEN EX™ Rubber Lug

SPECIAL FEATURES: ASTM F 2413-05 M/I/75/C/75 Steel Toe. Electrical Hazard. [Tested For and Meets CAN/CSA-Z195 18,000 Volts Electric Shock Resistance Standard](#). Abrasion-Resisting Rubber Toe and Heel Bumpers.

M 7-12, 13, 14

W 7-12, 13, 14



804-4128

6" BROWN GENERATION FLEX™ SAFETY

UPPER: Dark Brown Grizzly Oil-Tanned Leather

CONSTRUCTION: Net Fit Goodyear Welt

LINING: Perforated Dri-Lex®

INSOLE: Polyurethane Removable Insert/Special EVA Cushion Flex

MIDSOLE: Molded Polyurethane **SHANK:** Composite

OUTSOLE: Generation flex™ Dual Density Rubber

SPECIAL FEATURES: ASTM F 2413-05 M/I/75/C/75 Steel Toe. Electrical Hazard. [Tested For and Meets CAN/CSA-Z195 18,000 Volts Electric Shock Resistance Standard](#). Flexible Welt Net Fit Outsole

M 7-12, 13, 14

W 7-12, 13, 14



804-4129

8" BROWN GENERATION FLEX™ SAFETY

UPPER: Dark Brown Grizzly Oil-Tanned Leather

CONSTRUCTION: Net Fit Goodyear Welt

LINING: Perforated Dri-Lex®

INSOLE: Polyurethane Removable Insert/Special EVA Cushion Flex

MIDSOLE: Molded Polyurethane **SHANK:** Composite

OUTSOLE: Generation flex™ Dual Density Rubber

SPECIAL FEATURES: ASTM F 2413-05 M/I/75/C/75 Steel Toe. Electrical Hazard. [Tested For and Meets CAN/CSA-Z195 18,000 Volts Electric Shock Resistance Standard](#). Flexible Welt Net Fit Outsole

M 7-12, 13, 14

W 7-12, 13, 14



814-4128

6" BROWN GENERATION FLEX™ NON-SAFETY

814-4129

8" BROWN GENERATION FLEX™ NON-SAFETY

Weinbrenner Shoe Co.

108 S. Polk St. Merrill, Wisconsin
1-800-826-0002 • www.weinbrennerusa.com
An ISO 9001 Certified Shoe Company

OPTIONAL STOCKED STYLES



M 8 1/2-11, 12, 13
W 8 1/2-11, 12, 13



M 7-12, 13, 14
W 7 1/2-12, 13



814-4005

BROWN OXFORD NON-SAFETY

814-4010

6" BROWN NON-SAFETY



M 8 1/2-11, 12, 13
W 8 1/2-11, 12, 13



M 8 1/2-11, 12, 13
W 8 1/2-11, 12, 13

UPPER: Brown Oiled Nubuck Leather
CONSTRUCTION: Goodyear Storm Welt
LINING: Brushed Nylon
INSOLE: Wrapped Cushion
MIDSOLE: Rubber
SHANK: Steel
OUTSOLE: Oil-Resisting EVA Lug



814-4012

8" BROWN NON-SAFETY

814-4013

BROWN WELLINGTON NON-SAFETY



804-4010

6" BROWN GEN EX™ SAFETY

UPPER: Brown Oiled Nubuck Leather
CONSTRUCTION: Goodyear Strom Welt
LINING: Brushed Nylon
INSOLE: Wrapped Cushion
MIDSOLE: Rubber
SHANK: Steel
OUTSOLE: Oil-Resisting EVA Lug

SPECIAL FEATURES: ASTM F 2413-05 M/1/75/C/75 Steel Toe. Electrical Hazard. Tested For and Meets CAN/CSA-Z195 18,000 Volts Electric Shock Resistance Standard.

M 7-12, 13, 14
W 7-12, 13



804-4011

8" BROWN GENERATION FLEX™ SAFETY

UPPER: Brown Oiled Nubuck Leather
CONSTRUCTION: Goodyear Strom Welt
LINING: Brushed Nylon
INSOLE: Wrapped Cushion
MIDSOLE: Rubber
SHANK: Steel
OUTSOLE: Oil-Resisting EVA Lug

SPECIAL FEATURES: ASTM F 2413-05 M/1/75/C/75 Steel Toe. Electrical Hazard. Tested For and Meets CAN/CSA-Z195 18,000 Volts Electric Shock Resistance Standard.

M 8 1/2-11, 12, 13
W 8 1/2-11, 12, 13



804-4012

8" BROWN GENERATION FLEX™ SAFETY

UPPER: Brown Oiled Nubuck Leather
CONSTRUCTION: Goodyear Strom Welt
LINING: Brushed Nylon
INSOLE: Wrapped Cushion
MIDSOLE: Rubber
SHANK: Steel
OUTSOLE: Oil-Resisting EVA Lug

SPECIAL FEATURES: ASTM F 2413-05 M/1/75/C/75 Steel Toe. Electrical Hazard. Tested For and Meets CAN/CSA-Z195 18,000 Volts Electric Shock Resistance Standard.

M 8 1/2-11, 12, 13
W 8 1/2-11, 12, 13



Weinbrenner Shoe Co.

108 S. Polk St. Merrill, Wisconsin
1-800-826-0002 • www.weinbrennerusa.com
An ISO 9001 Certified Shoe Company